


## SHOCKICEL® SHOCK

### SHOCKICEL® SHOCK

#### GENERAL FEATURES:

- Excellent shock absorption.
- Long life material.
- Soft touch and comfort.
- Closed cell foam.
- Not moldeable.



Reference	Thickness	Sheet Size	Colour
20900401	1,50 mm	2000 x 1000 mm	Blue ●
20900403	3,00 mm	2000 x 1000 mm	Blue ●

## SHOCKICEL® TRANSPIRA


### SHOCKICEL® TRANSPIRA

#### VALUES OF MATERIAL

Shore A. 12 ±

#### GENERAL FEATURES:

- High comfort for the life of the foot orthotic
- Really breathable.
- commonly used in the prevention of neuropathic diabetic foot ulcers -Very eglued.



Reference	Thickness	Wide Roll	Long meters	Colour
22930401	1,50 mm	1000 mm	46 mts	Blue ●
22930403	3,00 mm	1000 mm	31 mts	Blue ●

## SHOCKICEL® RED MEMORY




### SHOCKICEL® RED MEMORY

#### GENERAL FEATURES:

- Deep memory foam
- Reproduction of the foot discharges.
- Slow recovery.
- Breathable.
- Impact absorption

Reference	Thickness	Wide Roll	Long meters	Colour	
24939403	3,00 mm	1000 mm	31 mts	Red	<span style="color: red;">●</span>
24939406	6,00 mm	1000 mm	23 mts	Red	<span style="color: red;">●</span>

## DUAL LAYERS



### SHOCKICEL® TRANSPIRA & RED MEMORY

#### GENERAL FEATURES:

- Impact absorption, elasticity and malleable to the foot.
- This material has a larger open cell than that of our competitors material making it more transpirable.  
Using our material there are no unpleasant odours. The foot stays fresh and dry
- This foam does not transmit heat to the feet as do EVA and PU polyurethanes

Reference	Thickness	Wide Roll	Long meters	Colour	
25939401	1,50/3,00 mm	1000 mm	23 mts	Blue/ Red	<span style="color: blue;">●</span> <span style="color: red;">●</span>
25939403	3,00/3,00 mm	1000 mm	23 mts	Blue/ Red	<span style="color: blue;">●</span> <span style="color: red;">●</span>

## SHOCKICEL® TPU COMPOSITE



### SHOCKICEL® COMPOSITE Rigid foot orthotics

Typical molding temperatures: 240°C

#### GENERAL FEATURES:

- Incredible easiness of moulding.
- Fusion by means of temperature.
- If does not need special glues.
- vacuum thermoforming

Reference	Thickness	Size Sheet mm	Colour	
21002112	1,25 mm	620 X 1000 mm	Silver	○
21002115	1,50 mm	620 X 1000 mm	Silver	○
21002120	2,00 mm	620 X 1000 mm	Silver	○

## SHOCKICEL® PP COMPOSITE



### SHOCKICEL® COMPOSITE FLEX

Typical molding temperatures: 200°C

#### GENERAL FEATURES:

Fuses by heat, which allows to manufacture insoles with the minimum thickness.

The user will enjoy a comfort, not possible by now with most of insoles of the market and with the best mechanical properties.

Reference	Thickness	Size Sheet mm	Colour	
21004112	1,25 mm	860 x 1000 mm	Black	●
2100415	1,50 mm	860 x 1000 mm	Black	●



### SILICONE SHEET

Reference	Thickness	Sheet Size	Colour	
21021200	1,00 mm	1200 x 1000 mm	White	○
21001200	1,00 mm	120 x 140 mm	White	○

Indispensable accessory to work Shockicel Composite. The silicon sheet allow to maintain the temperature whileout the vacuum.